



Knowledge Beyond Measure.

Aerotrak® Portable Particle Counter

MODEL 9500



The TSI® AeroTrak® 9500 Portable Particle Counter offers best-in-class features and versatility.

Perform ISO 14644-1 classifications and complete certifications of EU GMP facilities by sampling 1 m³ of air in just 10 minutes! Particle count data can be conveniently viewed on screen, downloaded using TrakPro™ Lite Secure Software, or printed directly to the integrated printer. Compatible with TSI® accurate ventilation probes that measure air velocity/temperature/RH, the Model 9500 is a complete solution for your certification needs. The combination of an optional electronic filter scanner with up to 26 ft of tubing, makes this the best instrument for in-place filter testing.

This particle counter can generate pass/fail reports for ISO 14644-1, EU GMP Annex 1, and FS209E, via the onboard printer and the supplied TrakPro™ Lite Secure Download Software. Multiple particle counter configurations can be conveniently stored and uploaded as needed. It can be used as a stand-alone particle counter or integrated into a facility monitoring system like TSI® FMS 5.

The Model 9500 complies with all the stringent requirements set forth in ISO 21501-4. It is calibrated with NIST traceable PSL spheres using TSI's world-class Classifier and Condensation Particle Counters, the recognized standard for particle measurements. Backed with a standard two-year warranty and TSI's long-standing reputation for high quality, there are no other particle counters like it on the market today.

Features and Benefits

- 0.5 to 25 µm size range
- Up to six channels of simultaneous data
- 3.53 CFM (100 L/min) flow rate
- Complies with all requirements of ISO 21501-4
- Best choice for filter testing in cleanrooms
- Data storage: 250 zones, 999 locations, and 10,000 samples
- USB, USB Storage Device and Ethernet data transfer
- Industry's loudest audible alarm
- Easy icon-driven touch screen operation
- Onboard reports for ISO-14644-1, EU GMP Annex 1, and FS209E
- External certification reports via TrakPro™ Lite Secure Software
- Barcode scanner supports recall of specific Recipe and Zone configurations
- Displays up to three environmental parameters
- Stainless steel enclosure
- Lightweight
- Stand-alone or integrate into a facility monitoring system
- Battery life provides up to 3 hours of continuous operation



Specifications

Aerotrak® Portable Particle Counter

Model 9500

Size Range

0.5 to 25 µm

Particle Channel Sizes

0.5, 0.7, 1.0, 3.0, 5.0, 10.0 µm

Size Resolution

<15% @ 0.5 µm (per ISO 21501-4)

Counting Efficiency

50% at 0.5 µm, 100% for particles > 0.75 µm (per ISO 21501-4 and JIS)

Concentration Limit

425,000 particles/ft³ (15,000,000/m³)
@ 10% coincidence loss

Light Source

Long life laser diode

Zero Count

<1 count per 5 minutes (per ISO 21501-4 and JIS B9921)

Flow Rate

3.53 CFM (100 L/min) ±5% accuracy (meets ISO 21501-4 and JIS B9921)

Flow Rate Control

Electronic, automatic closed loop (patented* flow control technology)

Sample Tube Extension

Up to 26.2 ft (8 m)

Sampling Modes

Manual, automatic, beep; cumulative/differential; count or concentration

Sampling Time

1 second to 99 hours

Sampling Frequency

1 to 9999 cycles or continuous

Exhaust

Internally HEPA filtered

Vacuum Source

Internal pump

Communication Mode

Modbus® TCP over Ethernet or USB

Audible Alarm

Built-in; >85 dB at 1 meter (adjustable)

Status Indicators

Low battery, flow, laser

Alarm Output

Dry contacts, closed when alarm is engaged

Alarm Limits

Programmable for all particle channels

Display

VGA 5.7-inch (14.5-cm) touch screen display

Languages

English, German, French, Spanish, Japanese, Chinese (simplified), Italian

Software

Compatible with TrakPro™ Lite Secure and FMS 5 Software

Printer

Built-in thermal printer (also available without printer)

Printer Output

Prints in all available languages

Environmental Sensor Interface

Supports TSI® Probe Models: 960, 962, 964, 966, (air velocity/temp/RH) and Temp/RH probe

External Chemical Resistance

Isopropyl alcohol, chlorinated solution, hydrogen peroxide

Unit ID

Configurable IP address

Security

2-level password protection to lock out usage and configuration

Data Storage

250 Zones
999 Locations
10,000 sample records including: date, time, six total particle size channels, flow status, and instrument status

Data Transfer

Via USB storage device, connection to TrakPro™ Lite Secure Software through Ethernet or USB cable, or optional TSI® FMS Software.

Reports

Provides Pass/Fail on ISO 14644-1, EU GMP, and FS209E reports

Calibration

NIST traceable using TSI® calibration system

Calibration Frequency

Recommended minimum of once per year

Dimension (H x W x D)

9.5 in. x 9.0 in. x 9.2 in.
(24.1 cm x 23.0 cm x 23.2 cm)
(without isokinetic inlet)

Weight

14.2 lbs (6.44 kg) with two batteries

Power

110 to 240 VAC universal power supply

Battery

Removable/rechargeable Li-Ion batteries (2 battery slots)

Battery Life**

Up to 3 hours of continuous operation

Battery Recharge

5 hours (when idle)

External Surface

Stainless steel

Operating Range

36° to 95° F (2° to 35° C),
20% to 95% RH noncondensing

Storage Range

32° to 122° F (0° to 50° C),
up to 98% RH noncondensing

Standards

ISO 21501-4, CE, JIS B9921

Warranty

Two years

Included Accessories

Printed QuickStart guide, operating manual on CD, power supply, battery, barbed inlet, isokinetic probe, tubing, purge filter, printer paper, USB cable and TrakPro™ Lite Secure Software

Optional Accessories

Electronic filter scanning probe, basic filter scanning probe, TSI velocity probes, Temp/RH probe, additional battery, dual port external battery charger, isokinetic probes, sample tubing, carrying case

* Patent Number 6,167,107

** Battery life will vary based on setup and application.

Specifications are subject to change without notice.

AeroTrak, TSI and the TSI Logo are a registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.

Modbus is a registered trademark of Modicon, Inc.



Knowledge Beyond Measure.

TSI Incorporated - Visit our website www.tsi.com for more information.

USA Tel: +1 800 874 2811
UK Tel: +44 149 4 459200
France Tel: +33 1 41 19 21 99
Germany Tel: +49 241 523030

India Tel: +91 80 67877200
China Tel: +86 10 8219 7688
Singapore Tel: +65 6595 6388