



### Features and Benefits

- AERO TRAK 7310: 0.3 to 25  $\mu\text{m}$
- AERO TRAK 7510: 0.5 to 25  $\mu\text{m}$
- 1 CFM (28.3 L/min) flow rate
- Up to four channels of simultaneous data
- ISO 21501-4 Compliant
- Ethernet (TCP/IP) and serial Modbus RTU output
- Power-over-Ethernet (PoE) or local power
- 3,000 sample record storage
- Static or dynamic IP address (DHCP)
- Local or remote configuration via web browser
- RoHS Compliant
- Low outgassing and ionics using 3M™ Adhesive Technology
- Stainless steel enclosure
- Optional Temp/RH probe
- Optional external alarm output
- Smallest remote particle counter in the market (0.3  $\mu\text{m}$  @ 1 CFM)

### AERO TRAK™ Remote Particle Counters Models 7310 & 7510

The TSI AERO TRAK 7310 and 7510 Remote Particle Counters offer the most features and flexibility out of any remote particle counter on the market today. Integration is easy using either Ethernet (TCP/IP) or serial Modbus RTU communications. The instrument can be powered over its Ethernet connection (Power-over-Ethernet) to simplify installation, or via a local power supply. Configuration can be done locally with a PC or via a web browser.

These particle counters can also store up to 3,000 sample records providing data redundancy. Each instrument reports up to four particle sizes simultaneously and other key information such as laser current, background light level, date of last calibration, serial number and date of manufacture for easy warranty management.

Digital calibration allows for consistency when managing a large number of instruments. With the optional Temp/RH sensor, users can save cabling and powering a separate sensor into a monitoring or building automation system. Each TSI AERO TRAK Remote Particle Counter also includes an alarm output which allows users to alarm directly from the particle counter.

Backed with a standard two-year warranty and TSI commitment for superior service and support, there is no other remote particle counter on the market today with such features and benefits.



## Specifications

## Models 7310 &amp; 7510

## AEROTrAK Remote Particle Counters



Features	7310	7510
Size Range	0.3 to 25 µm	0.5 to 25 µm
Channel Sizes	Standard: 0.3, 0.5 µm Optional: 0.3, 0.5, 0.7, 1.0 µm Optional: 0.3, 0.5, 1.0, 5.0 µm Additional channel sizes available	Standard: 0.5, 5.0 µm Optional: 0.5, 0.7, 1.0, 5.0 µm Additional channel sizes available
Counting Efficiency	50% at 0.3 µm; 100% for particles > 0.45 µm (per ISO 21501-4 and JIS)	50% at 0.5 µm; 100% for particles > 0.75 µm (per ISO 21501-4 and JIS)
Concentration Limits	100,000 particles / ft <sup>3</sup> at 5% coincidence loss	200,000 particles / ft <sup>3</sup> at 5% coincidence loss
Light Source	Laser diode	
Zero Count Level	<1 count / 5 minutes (<2 particles / ft <sup>3</sup> ) (per ISO 21501-4 and JIS)	
Flow Rate	1 CFM (28.3 LPM) with ± 5% accuracy	
Calibration	NIST traceable using TSI calibration system	
Vacuum Requirements	External vacuum > 38.1 cm of Hg	
Communication Mode	Ethernet (TCP/IP) and serial Modbus output	
Data Storage	3,000 sample records	
Status Indicators	Power, service, sampling and Ethernet	
External Alarm Output	Normal open dry contact rated 0 to 60 V AC/DC 1 Amp	
Environmental Sensors	Optional Temp/RH probe 0° to 45°C ± 1°C; 10 to 90% RH ±5%	
External Surface	Stainless steel	
Power	Power-over-Ethernet (PoE compliant with IEEE 802.3af) or 12 VDC	
Dimensions (L x W x H)	11.5 cm x 4.1 cm x 7.2 cm	
Weight	0.43 kg	
Standards	CE, JIS B9921, ISO 21501-4	
Warranty	Two years. Extended warranties available	
Operating Conditions	10° to 40°C / 20% to 95% non-condensing	
Storage Conditions	-10° to 50°C / Up to 98% non-condensing	
Included Accessories	Operating manual on CD	
Optional Accessories	Power supply, isokinetic inlets, purge filter, Temp/RH probe, alarm cable, sample tubing, vacuum tubing, data cable and remote mounting bracket	

Specifications are subject to change without notice.

AEROTrAK, TSI, and the TSI logo are trademarks of TSI Incorporated. 3M is a trademark of 3M Company.

**TSI Incorporated** - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

<b>USA</b>	Tel: +1 800 874 2811	E-mail: info@tsi.com	Website: www.tsi.com
<b>UK</b>	Tel: +44 149 4 459200	E-mail: tsuuk@tsi.com	Website: www.tsiinc.co.uk
<b>France</b>	Tel: +33 491 11 87 64	E-mail: tsifrance@tsi.com	Website: www.tsiinc.fr
<b>Germany</b>	Tel: +49 241 523030	E-mail: tsigmbh@tsi.com	Website: www.tsiinc.de
<b>India</b>	Tel: +91 80 41132470	E-mail: tsi-india@tsi.com	
<b>China</b>	Tel: +86 10 8251 6588	E-mail: tsibeijing@tsi.com	
<b>Singapore</b>	Tel: +65 6595 6388	E-mail: tsi-singapore@tsi.com	



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website [www.tsi.com](http://www.tsi.com) for more detailed specifications.