


MSP Turbo II[™] Vaporizer

Model 2852PE



Low flow, piezo valve

MSP's Turbo II™ Vaporizer 2852PE is designed for high-precision microelectronic applications that require low to mid vapor flow rates. Based off of the field proven, highly reliable, and low-maintenance MSP Turbo™ Vaporizers, the new 2852PE provides stable vapor concentrations while maintaining a very small footprint. The 2852PE also features an on-board flow control valve for extremely fast flow-rate response.

Dimensions 198 mm x 79 mm x 114 mm (7.8" x 3.1" x 4.5")

Weight 2.5 kg (5.6 lb)

Fittings (on the unit)

Carrier Gas Inlet 1/4 inch VCR female split nut

Liquid Inlet 1/8 inch VCR female

Vapor Outlet 1/4 inch VCR female split nut Compressed Air 4 mm instant tube fitting

Wetted Parts SS 316, PEEK, PTFE, Elgiloy®, FFKM

Leak Integrity≤ 1x 10^{-8} Pa·m³/s HeliumHeater Power Requirements¹208 $V_{AC'}$ 60 Hz, 450 WCarrier GasInert gas recommended

Max Carrier Gas Flow¹ 2.0 standard liters/min N₂ @ 50 psig

Max Liquid Flow² 7 g/min (TEOS or equivalent)

System Pressure Limit 150 psig

Compressed Air 90 to 110 ps

Compressed Air 90 to 110 psig
Temperature Range³ 40°C to 180°C

Temperature Sensor 2 type K thermocouples


³ Appropriate venting is required.


¹ Max Carrier Flow, Heater Power (W) and Line Voltage are factory adjustable, visit www.tsi.com/contact to request more information.

² Max. liquid flow is process dependent. The spec assumes a vaporizer temperature of 180°C, max. carrier gas flow and pressure <50 Torr immediately downstream of the vaporizer.




FACILITY DIMENSIONS











All specifications are subject to change without notification.

ELGILOY® Registered Trademark of Elgiloy Specialty Metals.

The MSP logo is a trademark of MSP Corporation. TSI and the TSI logo are registered trademarks of TSI Incorporated.



 $\textbf{MSP-Visit our website } \textbf{www.tsi.com/msp} \ \text{for more information}.$

5910 Rice Creek Parkway, Suite 300 Shoreview, Minnesota 55126, U.S.A. **Tel:** 651.287.8100